

imageRUNNER ADVANCE

6055/i
6065/i
6075/i

The next level in
office productivity.

you can

Move your business forward with our most advanced series of multifunctional black and white office devices. Boosting office productivity and transforming document workflows, they offer advanced security capabilities and outstanding environmental credentials.



55 - 75

PPM PPM
MONO

PERSONAL USER
INTERFACE

UP TO 7,700
SHEET PAPER
CAPACITY

EXCEPTIONAL
SCANNING
CAPABILITY

ADVANCED
FINISHING
CAPABILITIES

MODULAR
DESIGN

Productivity

- Highly intuitive 8.4" colour touch-screen user interface
- Create "one-touch" buttons to execute common tasks
- High speed duplex scanning up to 200 ipm
- Seamless scanning into business applications
- Integrated software options provide powerful end-to-end workflow solutions

Environmental

- Excellent energy efficiency: as little as 1.5 watts power consumption in sleep mode
- Energy Star certified
- Incorporates recycled materials and Bio plastics

Security

- Advanced security features spanning document confidentiality, integrity and availability
 - Seamless integration with Canon uniFLOW OM solution
 - Compliance with Common Criteria at EAL3 level*
- *Requires optional HDD Data Encryption & Mirroring Kit

Finishing & Quality

- Advanced finishing (booklet & staple finishing, C & Z folding, inserting, hole punching)
- Superb 1200 dpi print quality
- Optional Genuine Adobe PostScript & Fiery based RIP

 **imageRUNNER**
ADVANCE

Canon

Specifications: imageRUNNER ADVANCE 6055/i 6065/i 6075/i

BASIC SPECIFICATIONS Type Maximum Original Size Copy Sizes Resolution Copy/Print Speed Enlargement/ Reduction First copy time Warm-Up Time Multiple Copies/Prints Duplexing Paper weight Paper Capacity Processor speed Memory Hard Disk Drive Display Interface Network Protocols Power Supply Power Consumption Dimensions (W x D x H) Installation space (W x D) Weight	Console A3 Cassette 1, 2: A4 Cassette 3, 4: A3 to A5R, Free size (139.7 x 182 to 297 x 487.7) Stack Bypass: A3 to A5R, Free size (100 x 148 to 297 x 487.7) Reading: 600dpi x 600dpi, Copying: 1200dpi x 1200dpi Printing: 1200dpi x 1200dpi, 256 Gradations A4: 55 ppm (iR-ADV 6055/i), 65 ppm (iR-ADV 6065/i), 75 ppm (iR-ADV 6075/i), A3: 32 ppm (iR-ADV 6055/i), 32 ppm (iR-ADV 6065/i), 37 ppm (iR-ADV 6075/i) Zoom: 25 - 400% Fixed: Zoom Ratio 25%, 50%, 70%, 100%, 141%, 200%, 400% 3.3 seconds (iR-ADV 6055/i, iR-ADV 6065/i), 3.1 seconds (iR-ADV 6075/i) 38 seconds or less 1 to 9999 sheets Standard Automatic Cassettes: 52 to 220gsm, Stack Bypass: 52 to 256gsm Duplex: 52 to 220gsm Standard: 1,500 sheets x 2 Cassettes (3,000 sheets), 550 sheets x 2 Cassettes (1,100 sheets) Stack Bypass: 100 sheets, Optional: Side Paper Deck: 3,500 sheets, Max paper capacity: 7,700 sheets 1.2GHz 1.5GB (optional 512MB available) Standard 80GB, Expandable up to 250GB 8.4" TFT SVGA Colour Touchscreen, Optional 10.4" TFT SVGA Colour Touchscreen Ethernet (1000Base-T/100Base-TX/10Base-T), Wireless LAN(IEEE802.11b/g (Optional), USB2.0 TCP/IP* (LPD/ Port 9100/ WSD/ IPP/ IPPS/ SMB/ FTP), IPX/ SPX (NDS, Bindery), AppleTalk, *IPv4/IPv6 support 220-240V, 10A 50/60Hz 2.2 kW Max. 645mm x 770mm x 1220mm 942mm x 1289mm Approx. 235kg
PRINT SPECIFICATIONS Page Description Language(s) Resolution Fonts Supported Operating Systems	UFR II (Standard on all models), PCL5e/6: (Standard for i models, Optional for non i-models with Canon PCL Printer Kit-A1), Adobe PostScript 3 (Optional on all models with Canon PS Printer Kit-A1) 1200dpi x 1200dpi, 600dpi x 600dpi PCL fonts: 93 Roman, 10 Bitmap, 2 OCR, PS fonts: 136 Roman UFR II: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) PCL: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008 / Windows 7/ Server 2008 R2 PS: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) MAC-PPD: MAC OS 9.1 or later, MAC OS X (10.2.8 or later)
FIERY BASED PRINTING Name Page Description Language(s) Resolution Memory Hard Disk CPU Fonts Supported Operating Systems Interface Network Protocol	imagePASS-U1 (Optional) Adobe PostScript 3, PCL6 / PCL5e 1200dpi x 1200dpi, 600dpi x 600dpi, 2GB 80GB Intel Core Duo T2500, 2.0GHz PS: 136 Adobe PS Fonts, PCL: 113 PCL Fonts Windows 2000 (Printer driver only)/ XP(SP3)/Server 2003 (SP2)/ Server 2008(SP2)/ Vista(SP2)/ Vista SP1/ Windows 7 (Printer driver only), MAC OS (10.4 or later) Ethernet (1000Base-T/100Base-TX/10Base-T), USB, D-sub 15-pin connector TCP/IP (LPD/ Port 9100/ IPP/ SMB/ FTP), AT/ DDP(AppleTalk)
SCAN SPECIFICATIONS Optional/Standard Scan Speed Scan Resolution Pull Scan	Requires optional Duplex Colour Image Reader Unit-C1 Scan (Single side): A4 120 ipm 300dpi (BW), 85 ipm 300dpi (Colour), Scan (Double side): A4 200 ipm 300dpi (BW), 100 ipm 300dpi (Colour) 100dpi, 150dpi, 200 x 100dpi, 200dpi, 200 x 400dpi, 300dpi, 400dpi, 600dpi (600dpi colour scanning requires optional Memory Type B - 512MB) Via Network TWAIN Driver (75 to 600 dpi Black & White and Colour) Pull Scan Supported OS: Windows 2000/ Windows XP/ Windows Server 2003/ Windows Vista/ Windows Server 2008/ Windows 7, (32 bit, 64 bit in compatibility mode)
SEND SPECIFICATIONS Optional/Standard Destinations Address book File Format Universal Send Feature Sets:	Requires optional Duplex Colour Image Reader Unit-C1 E-Mail/ Internet FAX (SMTP), PC (SMB, FTP), WebDAV LDAP, Local (Max.1800) TIFF, JPEG, PDF, XPS, High compression PDF/XPS, PDF/A-1b, Optimize PDF for Web Universal Send Advanced Feature Set-E1 (option): Outline PDF (Trace & Smooth), Searchable PDF/XPS, Reader Extensions PDF Universal Send Security Feature Set-D1 (option): Encrypted PDF, Device Signature PDF/XPS, Universal Send Digital User Signature Kit-C1 (option): User Signature PDF/XPS

DOCUMENT FEEDER Colour Image Reader Name Paper size Paper weight Max. Number of originals Scanning speed (max.) Dimensions (WxDxH) Weight	Duplex Color Image Reader Unit-C1 (Optional) A3, A4, A4R, A5, A5R Single sided original: 38 to 220 gsm, Double sided original: 64 to 220 gsm 300 sheets (80 gsm) Copy (Single side): A4 120 ipm 600dpi (B&W) Scan (Single side): A4 120 ipm 300dpi (B&W), 85 ipm 300dpi (Colour) Copy (Double side): A4 120 ipm 600dpi (B&W) Scan (Double side): A4 200 ipm 300dpi (B&W), 100 ipm 300dpi (Colour) 635mm x 605mm x 253mm Approx. 39.4kg
PAPER DECK UNIT-A1 Paper Size Paper Weight Paper Capacity Dimensions (W x D x H) Weight	A4 52 to 220 gsm 3,500 sheets (80 gsm) 323mm x 583mm x 570mm Approx. 37kg
PAPER DECK UNIT-D1 Paper Size Paper Weight Paper Capacity Dimensions (W x D x H) Weight: Approx	A3, A4, A4R 52 to 220 gsm 3,500 sheets (80 gsm) 601mm x 621mm x 570mm 57 kg
STAPLE FINISHER-E1 BOOKLET FINISHER-E1 Number of Trays Tray Capacity Paper Weight Staple Position Staple Capacity Booklet Stitch Paper Size Booklet Stitch Staple Capacity Dimensions (W x D x H) Weight	3 Tray A: A4/A5R 250 sheets, A3/A4R 125 sheets, Tray B: A4/A5R 1,300 sheets, A3/A4R 650 sheets, Tray C: A4 2,450 sheets, A5R 1,700 sheets, A3/A4R 650 sheets 64 to 105 gsm Corner, Double, Booklet Stitch (Booklet Finisher only) A4: 50 sheets, A3/A4R : 30 Sheets A3, A4R (Booklet Finisher-E1 only) 16 sheets (64 pages, 64-81gsm) (Booklet Finisher-E1 only) Staple Finisher-E1: 748mm x 656mm x 1121mm Booklet Finisher-E1: 748mm x 656mm x 1121mm Staple Finisher-E1: Approx. 48kg Booklet Finisher-E1: Approx. 70.5kg
PUNCHER UNIT/S (All Puncher Units require either the Booklet Finisher-E1 or Staple Finisher E1)	External 2 Hole Puncher-A1: 2 holes, External 4 Hole Puncher-A1: 4 holes (Swedish), External 2/4 Hole Puncher-A1: 2 holes, 4 holes (French)
DOCUMENT INSERTION/ FOLDING UNIT-H1 Number of insertion trays Paper Size / Paper Weight Insertion Capacity C-Fold Paper Size/ Weight Z-Fold Paper Size/ Weight Output Capacity Dimensions (W x D x H) Weight	Requires either Booklet Finisher-E1 or Staple Finisher-E1 1 Tray A3, A4, A4R / 60 to 256 gsm 100 sheets (80 gsm) A4R/ 60 to 105 gsm A3, A4R/ 60 to 105 gsm 40 Sheets 662mm x 679mm x 1242mm Approx. 76kg
DOCUMENT INSERTION UNIT-L1 Number of insertion trays Insertion Paper Size Paper Weight Insertion Capacity Dimensions (W x D x H) Weight	Requires either Booklet Finisher-E1 or Staple Finisher-E1 1 Tray A3, A4, A4R 60 to 256 gsm 100 sheets (80 gsm) 662mm x 679mm x 1242mm Approx. 40kg
ADDITIONAL OPTIONS	Printer Cover-B1, Stamp Ink Cartridge-C1, ADF Access Handle-A1 Direct Print Kit (for PDF/XPS)-H1, Barcode Printing Kit-D1, Data Erase Kit-C1, HDD Data Encryption & Mirroring Kit-C2, Encrypted Printing Software-D1, Secure Watermark-B1, Web Access Software-H1, Access Management System Kit-B1, Expansion Bus-F1, Wireless LAN Board-B1, IPsec Board-B2, 2.5inch/80GB HDD-C1, 2.5inch/250GB HDD-D1, Removable HDD Kit-AD1, Document Scan Lock Kit-A1, Seequence compose (For IMAGEPASS-U1), Seequence impose (For IMAGEPASS-U1), Seequence Suite (For IMAGEPASS-U1), REMOVABLE HDD KIT-B4 (For IMAGEPASS-U1), Super G3 FAX Board-AF1, Super G3 2nd Line Fax Board-AF1, Remote Fax Kit-A1, Tab Feeding Attachment Kit-B1, Staple-J1, Staple Cartridge-D3, Shift Tray-E1, Copy Tray-Q1, Upright Control Panel-A1, Card Reader-C1, Copy Card Reader Attachment-A2, Utility Tray-A1, Control Panel Sheet-B1, Remote Operator's Software Kit-B1, Voice Guidance Kit-F1, Multimedia Reader/Writer-A1, Serial Interface Kit-K1
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final are subject to change without notice. * and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.	



Canon Inc.
www.canon.com

Canon Europa N.V.
www.canon-europe.com

English-UK Edition 00000
© Canon Europa NV 2010